

Product Description

Use high-performance COB LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

Luminaire

Structure	Adjustable Down Light LED
Model No.	IBSP158-PIN
Wattage	8W 15W
Luminous Flux	>600lm 1125lm
Beam	15° 24° 36°
IP Ratings	IP65
Material	Die-casting alu. trim and heatsink.
Finish	Matt white or black trim

Installation

Suitable for 5~18 mm thick ceiling board


LEDs

Brand	Bridgelux Cree
Type	COB
Color Temp	2700K 3000K 3500K 4000K 5000K 5700K 6500K
CRI	80 90


Control Gear

Remote constant current LED driver	
Brand	Lifud Eaglerise BOKE
Input Voltage	220~240Vac 100-240Vac
Dimming	Non Dim Dim
Remarks	Flicker-free,PF 0.5 0.9

Photometrics



Ra>80



Job/Project

Location

Fixture Ref.

Quantity

Remarks

Picture



Line art

Unit: mm

Model	Watts	D xH(mm)	Cutout(mm)
IBSP158CT085H81-PIN	8W	Ø93×H81mm	Ø85mm
IBSP158CT085H85-PIN	15W	Ø93×H85mm	Ø85mm
IBSP158CT075H81-PIN-TL	8W	Ø101×H81mm	Ø75mm
IBSP158CT075H85-PIN-TL	15W	Ø101×H85mm	Ø75mm