

Job/Project \_\_\_\_\_  
 Location \_\_\_\_\_  
 Fixture Ref. \_\_\_\_\_  
 Quantity \_\_\_\_\_  
 Remarks \_\_\_\_\_

## Product Description

Use high-performance COB LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

## Luminaire

Structure	Fixed Down Light LED
Model No.	IBSP101
Wattage	8W   10W   15W   25W   28W   40W
Luminous Flux	> 720lm   1000lm   1500lm   2500lm   2800lm   4000lm
Beam	15°   24°   38°   45°   60°
IP Ratings	IP65
Material	Die casting aluminum heatsink
Finish	White   black

## Installation

Installation  
 Suitable for 5~18 mm thick ceiling board


## LEDs

Brand	Bridgelux   Cree
Type	COB
Color Temp	2700K   3000K   3500K   4000K
CRI	5000K   5700K   6000K   6500K
CRI	80   90


## Control Gear

Remote constant current LED driver	
Brand	Eaglerise   Lifud   OEM
Input Voltage	220~240Vac   100-240Vac
Dimming	Non Dim   Dim
Remarks	Flicker-free, PF 0.5   0.9

## Photometrics



Ra>80



## Picture



**Line art**

Model	Watts	D xH(mm)	Cutout(mm)
IBSP101CT055	8W	Ø65 × H76mm	Ø55mm
IBSP101CT075H74	10W	Ø85 × H74mm	Ø75mm
IBSP101CT075H94	15W	Ø85 × H94mm	Ø75mm
IBSP101CT075H122	25W	Ø85 × H122mm	Ø75mm
IBSP101CT095	28W	Ø105 × H120mm	Ø95mm
IBSP101CT095H135	40W	Ø105 × H135mm	Ø95mm