

Product Description

Use high-performance COB LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

Luminaire

Structure	Adjustable Down Light LED
Model No.	IBSP133S
Wattage	8W 18W 25W 2×8W 2×18W 2×25W
Luminous Flux	> 560lm 1260lm 1750lm 1120lm 2520lm 3500lm
Beam	15° 24° 38° 60°
IP Ratings	IP 65
Material	Die casting aluminum heatsink
Finish	White black

Installation

Installation
Suitable for 5~18 mm thick ceiling board


LEDs

Brand	Bridgelux Cree
Type	COB
Color Temp	2700K 3000K 3500K 4000K 5000K 5700K 6000K 6500K
CRI	80 90


Control Gear

Remote constant current LED driver	
Brand	Eaglerise Lifud Boke
Input Voltage	220~240Vac 100-240Vac
Dimming	Non Dim Dim
Remarks	Flicker-free,PF 0.5 0.9

Photometrics



Ra>80



Job/Project	
Location	
Fixture Ref.	
Quantity	
Remarks	

Picture



Line art			
Model	Watts	L×W×H(mm)	Cutout(mm)
IBSP133SCT055	8W	L54×W54×H93mm	L57.5×W57.5
IBSP133SCT075	18W	L74×W74×H121mm	L77×W77
IBSP133SCT095	25W	L94×W94×H146mm	L97×W97
IBSP133SCT055-2H	2×8W	L116×W55×H90mm	L120×W60
IBSP133SCT075-2H	2×18W	L163×W74×H121mm	L170×W80
IBSP133SCT095-2H	2×25W	L207×W93×H142mm	L210×W97