

Job/Project

Location

Fixture Ref.

Quantity

Remarks

Product Description

Use high-performance COB LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

Luminaire

Structure	Fixed Down Light LED
Model No.	IBSP156
Wattage	10W 15W 25W
Luminous Flux	> 900lm 1350lm 2250lm
Beam	15° 24° 38° 45° 60°
IP Ratings	IP65
Material	Die casting aluminum heatsink
Finish	White black

Installation

Installation
Suitable for 5~18 mm thick ceiling board

LEDs

Brand	Bridgelux Cree
Type	COB
Color Temp	2700K 3000K 3500K 4000K 5000K 5700K 6500K
CRI	80 90



Control Gear

Remote constant current LED driver	
Brand	Eaglerise Lifud OEM
Input Voltage	220~240Vac 100-240Vac
Dimming	Non Dim Dim
Remarks	Flicker-free,PF 0.5 0.9

Picture



Photometrics



Line art

Model	Watts	D xH(mm)	Cutout(mm)	Lumen(lm/w)
IBSP156CT085H69	10W	Ø 70×H69mm	/	90-100
IBSP156CT085H89	15W	Ø 70×H89mm	/	90-100
IBSP156CT085H116	25W	Ø 70×H116mm	/	90-100
155CT085	/	Ø 93×H36mm	Ø 85mm	/
155CT075-TL	/	Ø 101×H33mm	Ø 75mm	/